

DOP Declaration of Performance LSP.docx**Declaration of Performance  
EN 14783 - Fully supporting products of steel**

Declaration of Performance number	B-2466
Company:	Lindab Profil AB
Article coding:	LSP
Geometrical tolerances:	EN 508-1
Product type:	Roof profile
Thickness and class:	0,6 class 1 0,8 class 1
Material:	Coated steel DX54+Z275 Zinc Magnesium DX56 + ZM310 Coated Aluminium 8111H41 Uncoated Aluminium 8111H2 Aluzinc DX54+A185
Side 1:	HDP 36 my for High durable polyester Uncoated for Zinc Magnesium and Aluzinc
Side 2:	SP 8 my for High durable polyester Uncoated for Zinc Magnesium and Aluzinc
Length of tile step:	Not applicable
Reaction to fire:	HDP, Class A2 - s2, d0 Zinc Magnesium, Aluminium and Aluzinc , Class A1 According to EN 13501-1
External fire performance:	$B_{roof(t1)}$ , $B_{roof(t2)}$ , $B_{roof(t3)}$ , $B_{roof(t4)}$
Resistance to concentrated force:	NPD
Förslöv 2021-02-23	

Carina Petersson, Product and Digital Development manager Lindab Profil AB